

DOLLE EXTRA SPECIAL MEASURE



ATTIC LADDER SPECIAL MEASURE - WITH 50 MM INSULATION

Special measure: Outer frame dimension: L:109,5-157,5 x B:47,6-97,6 Opening size: L:112-160 x B: 50-100
Casing length + width cannot exceed 240 cm

Dolle Extra with 50 mm insulation is a 3-section folding attic ladder, which requires no headroom or storage space in the loft. Draught excluder contained in casing and trapdoor with 50-mm insulation prevents loss of heat and draught. Nice finish with white-faced trapdoor. Non-slip treads for extra security. Specially developed height adjustment system. Casing and trapdoor with a rebate for extra tight closing. Ladder assembled for easy and quick installation.



PRODUCT DATA

PRODUCT NAME	Dolle Extra special measure
TYPE	3-section
MATERIAL	wood
PRODUCT-NO.	52300
FLOOR HEIGHT	Max. 332 cm
NUMBER OF TREADS	11-14
INSULATION	50 mm
MATERIAL (CASING)	Pine, untreated
THICKNESS (CASING)	18 mm
HEIGHT (CASING)	190 mm
CASING SIZE	special measure - (L):109.5 - 157.5cm x (W): 47.6 - 97.6cm
OPENING SIZE	special measure - (L):112 - 160cm x (W): 50 - 100cm Casing length + width cannot exceed 240cm.
MATERIAL (TRAPDOOR)	white HDF 2 x 3
INSULATION (TRAPDOOR)	50 mm
THICKNESS (TRAPDOOR)	56 mm
THICKNESS (TREADS)	18 mm
DEPTH (TREADS)	69 mm
WIDTH (TREADS)	400 mm
RISE (TREADS)	250 mm
MATERIAL (TREADS)	beech
MATERIAL (STRING)	pine
THICKNESS (STRING)	21 mm
DEPTH (STRING)	69 mm
MAX. HEIGHT CLOSED STAIR	36 cm
MAX. HEIGHT ARM, CLOSED STAIR CM	59,3 cm
MAX. USERWEIGHT	Tested by EN14975 up to 265 kg, work weight 150 kg
SPECIAL MEASURE	Yes
U-VALUE W/(M²K)	0,9 tested as building component
TEST	IFT Rosenheim EN12207 Class 4