

## Description

- ▲ Premier 3 section electric foldaway loft ladder with high craftsmanship and design.
- ▲ With its unique design the Skylark comes in a compact unit with trapdoor and fixed frame all of which are insulated and draft sealed.
- ▲ Fantastic U-Value of 0.71 W/m<sup>3</sup>K.
- ▲ The ladder is made from beech hardwood.
- ▲ To operate just push and hold the button on your remote control and watch the unit open and unfold. No manual effort needed.
- ▲ The Skylark is supplied with one remote control and a power pack with battery backup in case of a power outage.
- ▲ Supplied with two handrails.
- ▲ Ladder width measures 380mm.
- ▲ Distance between the ladder steps measures 230mm for a safe climb.
- ▲ Max floor to ceiling height of 3200mm.
- ▲ Frame length of the Unit (Minimum: 1200mm to Maximum: 2000mm).
- ▲ Frame width of the Unit available in 5 sizes - 650 / 700 / 750 / 800 & 850mm.
- ▲ Optional Lacquer finish to Skylark Ladder available.
- ▲ Made to measure sizes available on request.
- ▲ Skylark has a working load of 150 kg.
- ▲ Product includes a 10 year parts warranty.
- ▲ BS EN 14975 Standard.



**Skylark Electric Loft Ladder – Standard Sizes**

Ceiling Height	Min. Frame Length *	Frame Width *
Up to 2500mm	1200mm	650 / 700 / 750 / 800 / 850 mm
Up to 2900mm	1350mm	650 / 700 / 750 / 800 / 850 mm
Up to 3200mm	1500mm	650 / 700 / 750 / 800 / 850 mm

\* As these are the Frame sizes of the Unit, your structural loft opening size will need to be made 5mm longer in length and width to provide a fitting tolerance.