

Description

- Available in 3 diameters; 1200mm, 1400mm and 1600mm.
- The Misterstep Exterior Zink can be assembled to ascend clockwise or anti-clockwise.
- The standard unit comes with 12 treads plus a landing tread and can reach a floor height up to 2990mm. Heights of up to 3450mm can be achieved by using additional tread kits.
- Each rise is adjustable between 210mm to 230mm
- Min. opening sizes are 1250mm x 1250mm (1200mm diameter stair), 1450mm x 1450mm (1400mm diameter stair) and 1650mm x 1650mm (1600mm diameter stair).
- The stair is manufactured in steel with a hot-dip galvanised zinc finish. This protects against all weather conditions, making the Exterior Zink ideal for outdoor use.
- The handrail is a black plastic (Moplen) type and the balusters are 22mm steel with a hot-dip galvanised zinc finish.
- The tread angle for the Exterior Zink is at 30° for all 3 diameter choices.
- Optional upper floor balustrade for the Exterior Zink is also available.



Exterior Zink Stair Heights

| Staircase Height | No. of Risers | Tread Kits Required | Column Kits Required |
|-------------------|---------------|----------------------------|----------------------|
| 2100 mm - 2300 mm | 10 | - | - |
| 2310 mm - 2530 mm | 11 | - | - |
| 2520 mm - 2760 mm | 12 | - | - |
| 2730 mm - 2990 mm | 13 | STANDARD EXTERIOR ZINK KIT | |
| 2940 mm - 3220 mm | 14 | 1 | 1 * |
| 3150 mm - 3450 mm | 15 | 2 | 1 * |

* These Supplementary Column Kits (Centre Post) are required for the Exterior Zink Spiral Stair to achieve higher floor heights up to 3450mm