

Space-saving stairs Profi with wooden ladder

With this product, the high-quality space-saving stairs are equipped with a classic loft ladder. Our entry-level model for space-saving stairs with reduced functional requirements.



Energy label

- Component: 0.43 W/m²K*
- Bottom cover: 0.80 W/m²K*
- Top cover: 0.68 W/m²K*

* calculated by manufacturer according to DIN EN ISO 6946



Energy efficiency

- Air permeability Class 4 certified*
- Circumferential seal (triple)
- Thermal insulation in the covers

* certified by IFT Rosenheim according to DIN EN 12207/12114



Upper cover

- Metal flashing with galvanised sheet steel
- Closure: bar lock
- Prepared for customer-provided profile cylinder
- Edge glued for protection against weather
- incl. rubber hollow profile seal (double) with contact lip for roof membrane
- Side customer-provided insulation max. 40 mm
- Impermeable to driving rain (Class E1200)



Hatchbox / hatch cover

- Water repellent and treated with fungicide
- Including additional treads in the hatchbox
- Snap-lock bottom closure
- Installation allowance: 2 cm



Stairs

- Folding wooden stairway
- Treads: 33 cm. 8 cm deep
- Load bearing 150 kg per tread
- Adjustable inclination



Ready-to-install with standard accessories

- Handrail
- Protective cap feet
- Operating pole
- Cover strips, wood white
- Mounting screws

Options

- | | |
|---|--|
| Improved thermal insulation | |
| - Top cover: U value 0.38 W/m²K | |
| - Customer-provided insulation max. 80 mm | |

- | | |
|--|--|
| Improved thermal insulation | |
| - Top cover: U value 0.31 W/m²K | |
| - Customer-provided insulation max. 100 mm | |

