


## Description

- Available in 2 diameters; 1200mm and 1400mm.
- The standard unit comes with 11 treads plus a landing tread and can reach a floor height up to 2760mm. Heights of up to 3680mm can be achieved by using additional tread kits.
- Min. opening sizes are 1250mm x 1250mm (1200mm diameter stair) and 1450mm x 1450mm (1400mm diameter stair).
- The steel metalwork is available in White, Silver Grey, Red, Yellow, Blue or Green colour options.
- The steel treads come with self-adhesive grey rubber strips to create a non-slip surface.
- For the Gamia Metal in White, the handrail supplied will be a white polyethylene type. All other Gamia Metal colour options will come with a grey polyethylene handrail.
- The tread angle for the Gamia Metal is at 30° for both diameter choices.
- Optional upper floor balustrade for the Gamia Metal is also available.
- In order to comply with building regs, we can supply riser bars these ensure that the distance between the treads does not exceed 100mm.

White RAL 9010	Grey Silver	Red RAL 3003	Blue RAL 5002	Green RAL 6000	Yellow RAL 1023
					



### Gamia Metal Stair Heights

Staircase Height	No. of Risers	Tread Kits Required	Column Kits Required
2100 mm - 2300 mm	10	-	-
2310 mm - 2530 mm	11	-	-
2520 mm - 2760 mm	12	<b>GAMIA METAL STANDARD KIT</b>	
2730 mm - 2990 mm	13	1	-
2940 mm - 3220 mm	14	2	-
3150 mm - 3450 mm	15	3	1 *
3360 mm - 3680 mm	16	4	1 *

Height dimensions in the above chart are based on an individual rise from 210mm to 230mm.

Rises from 200 to 210mm & 230 to 240mm are possible with baluster adjustments made at the point of assembly.

\* These Supplementary Column Kits (Centre Post) are required for the Gamia Metal Spiral Stair to achieve higher floor heights up to 3680mm