

## Description

- Available in 3 diameters; 1200mm, 1400mm and 1600mm.
- The standard unit comes with 11 treads plus a landing tread and can reach a floor height up to 2760mm. Heights of up to 3450mm can be achieved by using additional tread kits.
- Min. opening sizes are 1250mm x 1250mm (1200mm diameter stair), 1450mm x 1450mm (1400mm diameter stair) and 1650mm x 1650mm (1600mm diameter stair).
- The steel metalwork is available in Black or Silver Grey colour options.
- The 38mm solid beech treads (*clear varnished*) are available in either a natural or dark walnut colour option.
- The handrail is a black polyethylene type and the balusters are 22mm steel (Black or Silver Grey colour options).
- The tread angle for the Gamia Wood is at 30° for all 3 diameter choices.
- Optional upper floor balustrade for the Gamia Wood is also available.
- In order to comply with building regs, we can supply riser bars these ensure that the distance between the treads does not exceed 100mm.

### Wood finishes



Natural Walnut

### Metal finishes



Black Silver grey



Black metalwork



Silver Grey metalwork

### Gamia Wood Stair Heights

Staircase Height	No. of Risers	Tread Kits Required	Handrail Kits Required	Column Kits Required
2100 mm - 2300 mm	10	-	-	-
2310 mm - 2530 mm	11	-	-	-
2520 mm - 2760 mm	12	GAMIA WOOD STANDARD KIT		
2730 mm - 2990 mm	13	1	-	1 *
2940 mm - 3220 mm	14	2	1	1 *
3150 mm - 3450 mm	15	3	1	1 *

Height dimensions in the above chart are based on an individual rise from 210mm to 230mm.

Rises from 200 to 210mm & 230 to 240mm are possible with baluster adjustments made at the point of assembly.

\* These Supplementary Column Kits (Centre Post) are required for the Gamia Wood Spiral Stair to achieve higher floor heights up to 3450mm