

Description

- ▲ Available in 3 Standard sizes to suit a floor to floor height up to 2880mm (**See Dolle Alufix Vertical - Specification Chart below**).
- ▲ Ready to fit concertina ladder, straight into your existing vertical opening or to a mezzanine floor area.
- ▲ Manufactured from high quality extruded aluminium alloy.
- ▲ Concertina stows in vertical position.
- ▲ Opening in the wall can be closed by a door (supplied by others) with a maximum thickness of 25mm.
- ▲ Deep and wide non-slip treads (80mm x 340mm).
- ▲ The Alufix Vertical Ladder is **not** spring assisted so its descent & ascent will need to be controlled with the use of an Operating Pole (*purchased in addition*).
- ▲ Supplied with a plastic pole hook as standard (*Operating Pole not included*).
- ▲ Tested according to EN 14975 (European Ladder Standard).
- ▲ Max working load: 100 kg.
- ▲ **Does not** come supplied with a Trapdoor / Hatch.



DOLLE ALUFIX VERTICAL - SPECIFICATION

Model	No. of Treads	Min Aperture (W) x (H)	Floor to Floor Height
AFV9	9	440 x 550mm	2100 - 2340mm
AFV10	10	440 x 580mm	2341 - 2600mm
AFV11	11	440 x 610mm	2601 - 2880mm