

DESCRIPTION

- ▲ The Gallery Stairway designed to tuck away, parallel to a wall when not in use.
- ▲ Standard model is constructed entirely of steel.
- ▲ Deluxe model is constructed of steel, with solid Beech treads. Beech treads available in a natural or medium walnut finish.
- ▲ Steel metalwork is available in either black, white or grey.
- ▲ Will suit floor to floor heights between 2000mm and 3000mm.
- ▲ Wheels fitted, with brakes, to allow stairway to be rolled into position and then secured.
- ▲ Handrails fitted to both sides, which extend above floor level to act as exit grab rails.
- ▲ Stairway mounted to a fixing plate (500mm (W) x 120mm (H)) positioned just below the floor level.
- ▲ Upper safety guard rails are available as an optional extra. They measure 1000mm high.



TECHNICAL INFORMATION

	STANDARD	DELUXE
METALWORK COLOUR	Black / White / Grey	Black / White / Grey
FLOOR HEIGHT	2000 – 3000mm	2000 – 3000mm
OVERALL STAIR WIDTH	440mm	440mm
LADDER ANGLE	68°	68°
TREAD DETAIL	Steel with self-adhesive non slip strips (black)	Solid Beech (natural or medium walnut shade)
TREAD DEPTH	70mm	120mm
USEABLE TREAD WIDTH	350mm	350mm
MIN. OPENING SIZE (LOFT)	1200 x 600mm	1200 x 600mm

