

Retractable stairway Exclusive

The patented scissors mechanism facilitates opening and closing the stairs at any time with very little effort (operation forces under 3 kg) - it is light as a feather to operate and yet extremely strong.



Energy label

- Component: $0.58 \text{ W/m}^2\text{K}^*$ (A)
 - DD design: $0.29 \text{ W/m}^2\text{K}$ (A+)
- * certified according to DIN ISO 12567-1 by IFT Rosenheim



Energy efficiency

- Air permeability Class 4 certified*
 - Circumferential seal
 - Thermal insulation in the cover
- * certified by IFT Rosenheim according to DIN EN 12207 / 12114



Hatchbox / cover

- Hatchbox and cover bottom side: white coating
- Snap-lock closure
- Box height: 24 cm
- Installation allowance 2 cm



Stairs

- Aluminium retractable stairways
 - Treads: 20-38 cm, 14 cm deep (made of pressure die-casting)
 - Treads: 43-33 cm, 16 cm deep (profile treads)
 - Load bearing 200 kg per tread
- We always deliver the maximum possible tread width



Ready-to-install with standard accessories

- Telescopic handrail included (opening length of 90 cm and above)
- Mounting screws
- Operating pole
- Snap-on white covering strips (plastic)



Optional

A version with projecting hinges can be supplied.* This allows you to apply an internal finish to the cover on site up to 15 mm or 10 kg/m².

* cover strips cannot be fitted

