

# Retractable stairway **Electro**

With this stairway, convenience across the generations is paramount. The low-noise electric motor securely extends and retracts the stairway. The stairway easily handles the extreme stresses and loads. We can therefore recommend it in the commercial sector.



## Energy label

- Component: 0.58 W/m<sup>2</sup>K\*
- DD design: 0.29 W/m<sup>2</sup>K
- \* certified according to DIN ISO 12567-1 by IFT Rosenheim



## Energy efficiency

- Air permeability Class 4 certified\*
- \* certified by IFT Rosenheim according to DIN EN 12207 / 12114
- Circumferential seal
- Thermal insulation in the cover



## Hatchbox / cover

- Hatchbox and cover bottom side: white coating
- Box height: 24 cm
- Installation allowance 2 cm



## Electronics

- 24 Volt drive
- Low noise with emergency power supply
- Control unit with one button (flush-mounted)
- Automatic limit stop and safety stop



## Stairs

- Aluminium retractable stairways
  - Treads: 25-38, 14 deep (made of pressure die casting)
  - Treads: 43-58, 16 deep (profile treads)
  - Load bearing 200 kg per tread
- We always deliver the maximum possible tread width



## Ready-to-install with standard accessories

- Telescopic handrail included (opening length of 110 cm and above)
- Mounting screws
- Operating pole
- Snap-on white covering strips (plastic)

