

Space-saving stairs with concertina stair Ecco



The benefits at a glance

- + Especially high-quality and weather-resistant hatchbox, which comes ready-to-install.
- + The entire element is water-repellent and is made to withstand the wind and weather.
- + Always a step ahead thanks to the Roto multi-point locking system.
- + The system can be installed flush without cover strips.
- + Ready-to-install with standard accessories: Snap-on white cover strips (PVC), operating rod with square shaft, mounting screws, professional installation package



Technology and product characteristics

Energy label	<ul style="list-style-type: none"> + Building element: 0.38 W/m²K* + Bottom cover: 0.77 W/m²K* + Top cover: 0.68 W/m²K*
Energy efficiency	<ul style="list-style-type: none"> + Circumferential seal (triple) + Air permeability Class 4 certified** + Thermal insulation in the covers / sandwich design
Top lid	<ul style="list-style-type: none"> + Metal flashing with galvanised sheet steel / aluminium sheet for structural opening widths of 90 cm and above + Lock using Roto NX hardware + Edge glued for protection against weather + incl. rubber hollow profile seal (double) with connection profile for roof membrane + Impermeable to driving rain (Class E1200) + Stop on right as standard
Hatchbox and cover	<ul style="list-style-type: none"> + Side customer-provided insulation max. 40 mm + White + Including additional treads in the hatchbox + Lock with 4-point interlock + Flush ceiling installation possible + Attractive design + lock flush without draw hooks + Installation allowance: 2 cm
Stairs	<ul style="list-style-type: none"> + Aluminium concertina stair + Treads: 28 - 33 cm / 8 cm deep (made of extruded section) + Load bearing 150 kg