

Description

- ▲ The Junior V is ideal for either new or existing openings. It offers flexible access to even the most unconventional vertical openings.
- ▲ The unit is supplied without a hatch, to operate alongside existing hatches or simply independently on a mezzanine floor.
- ▲ The Junior V is available in 4 standard sizes to suit a floor to floor height of up to 3500mm (*See Chart below*).
- ▲ The ladder is constructed from die-cast aluminium.
- ▲ The tread depth of the ladder measures 140mm.
- ▲ The tread width is dependent on the model choice and will either be 300mm or 350mm (*See Chart below*).
- ▲ The unit comes complete with Special brackets allowing the ladder to be deployed and retracted in vertical applications.
- ▲ When stored the concertina ladder stows in a vertical position.
- ▲ Opening in the wall can be closed by a door with a maximum thickness of 40mm (*not supplied*).
- ▲ Optional telescopic handrails are available.
- ▲ The Junior V is tested to EN 14975 (European Ladder Standard) with a 200kg per tread resilience.
- ▲ Complete with operating pole & full installation instructions.



JUNIOR V - SPECIFICATION

Model	No. of Treads	Min Aperture	Floor to Floor	Tread Width
JC9V	9	630 x 770mm	Up to 2640mm	350mm
JC10V	10	630 x 810mm	Up to 2930mm	350mm
JC11V	11	630 x 850mm	Up to 3230mm	350mm
JC12V	12	580 x 900mm	Up to 3500mm	300mm